

Set Flatec IV	Set /Each					
1 Art. No.	2	3	4	5	6	7
USU95-1800EF	1	2	2	4	1	1
USU95-2100EF	1	2	2	4	1	1
USU95-2300EF	1	2	2	5	1	1
USU95-2540EF	1	2	2	5	1	1

Also valid for polished version USU95-...EP

Beyerle US L.L.C., ABP-Byerle it's subsidiaries and agents are not responsible or liable for damage or injury to any persons or property due to improper installation of it's products.

All liabilities reside solely with the installer.



Comply with all general safety regulations when installing the sliding door fittings!

Installation to be completed by qualified licensed contractor.

Be sure to tighten all screw connections one week after starting to use the sliding door fittings!

Never use scouring agents to clean the sliding door fittings; rather use commercially available stainlesssteel cleaners!











V Install

90° At right angle























? Clarify questions






ABP ≜ beyerle

Beyerle US L.L.C. 5126 South Royal Atlanta Drive, Tucker, GA 30084 Phone (770) 349-6324, Fax (770) 934-3384, www.beyerle-us.com


Installation instructionsSliding door fittings **Flatec IV**

for wooden doors (max. 13/4" thickness)



Complete-sets Also valid for polished version USU95-...EP

•								
Set Flatec IV Artikel-No.	A inch	B inch	C Each	D inch	E max. inch	F inch	G inch	H max. inch (H=E-F+1")
USU95-1800EF	70 7/8"	20 1/4"	4	29 1/2" – 35 7/16"	98 7/16"	1/4"-3/8"	2 3/8"	99 1/8"
USU95-2100EF	82 11/16"	24 1/8"	4	35 13/16" – 39 3/8"	98 7/16"	1/4"-3/8"	2 3/8"	99 1/8"
USU95-2300EF	90 9/16"	20 1/16"	5	39 3/4" - 44 1/16"	98 7/16"	1/4"-3/8"	2 3/8"	99 1/8"
USU95-2540EF	100"	22 7/16"	5	44 1/2" - 49 3/16"	98 7/16"	1/4"-3/8"	2 3/8"	99 1/8"



Right to make technical changes reserved - Dimensions in inches - Version 03-2016 © by ABP-Beyerle GmbH

ABP beyerle